

## Product Highlights

### Designed for Surveillance

The switches features two modes: Standard Mode and Surveillance Mode, allowing the user to choose the interface most suitable for their needs

### Revolutionary Energy Efficiency

Innovative D-Link Green features help conserve energy without sacrificing performance so you can reduce operating costs and protect the environment

### Easy Management

A surveillance overview, ONVIF device support and video traffic optimization simplify the process of managing a surveillance network



## DGS-1100 MP/MPP Series Gigabit Ethernet PoE Switches

### Features

#### Physical

- High PoE budgets and support for IEEE 802.3bt 90 W PoE (DGS-1100 MPP Series)
- Fiber uplink ports for connection to a NVR or CMS center

#### Surveillance Network

- Easy deployment with automatic configuration
- Surveillance traffic optimization
- Auto-detect ONVIF devices
- Intuitive interface for monitoring and management
- Descriptive health diagnostics

#### Advanced Features

- IGMP Snooping
- Bandwidth control
- IEEE 802.1Q VLAN traffic segregation
- Port-based VLANs
- IEEE 802.1p
- Surveillance VLAN
- Voice VLAN
- G.8032 ERPS

#### Management Features

- Client-based utility or web-based GUI
- Built-in SNMP MIB
- Status Dashboard

The DGS-1100 MP/MPP Series is a range of switches designed to meet the surveillance requirements of small, medium, and enterprise businesses. Support for high-powered Pan Tilt Zoom (PTZ) cameras, and automatic Surveillance VLAN make the DGS-1100 MP/MPP Series ideal for IP surveillance deployments. A redesigned interface, a range of diagnostic and troubleshooting tools, and energy efficient technologies provide a flexible solution to your surveillance requirements.

### Easy to Deploy

An interactive setup wizard removes the complexity from installing the switch for the first time. It allows you to choose the web interface mode (Standard or Surveillance), the IP address allocation method (static or DHCP), and the administrator user name and password. This completes the initial setup of the switch and automatically configures features such as Loop Detection, DHCP Snooping, SNMP and Surveillance VLAN. An informative quick start guide shows you how to use the network diagram, and a network overview is displayed on the next page. D-Link and 3<sup>rd</sup> party devices are automatically detected and shown on the network overview page for easy administration.

### Surveillance Traffic Optimization

The DGS-1100 MP/MPP Series supports the automatic Surveillance VLAN feature. This automatically detects surveillance devices and puts them into the Surveillance VLAN, segmenting their traffic from the rest of the network. This ensures security of the data, but also gives the traffic a higher priority through the switch, reducing the chances of the video freezing or being delayed on live streams. A single switch can be used for both surveillance and data networks, removing the need for dedicated surveillance hardware and reducing maintenance costs.

## Intuitive Web Interface


A redesigned Surveillance interface makes surveillance features more accessible than ever. The choice between Standard and Surveillance modes can be made during switch set up, allowing the user to choose the interface that best suits their requirements. A network overview shows which devices are connected to which ports, and ONVIF device support allows the switch to recognize both D-Link and third party IP cameras and Network Video Recorders (NVRs). With monitoring, management, and troubleshooting tools built into a single interface, the DGS-1100 MP/MPP Series provides everything you need to manage your surveillance network.

## Easy Troubleshooting

The DGS-1100 MP/MPP Series features Loopback Detection and Cable Diagnostics to help network administrators find and solve network problems quickly and easily. Loopback Detection detects loops in the network, where multiple devices have been connected to each other and create a forwarding loop. The switch will identify the port causing the loop and shut the affected port down to avoid network instability. Cable Diagnostics can be used to remotely test the quality of copper cables, recognize the cable type, and detect cable errors.

## PoE Support

The DGS-1100 MP/MPP Series provides support for Power over Ethernet (PoE), reducing deployment time for IP cameras, VoIP phones, and access points. The DGS-1100-10MPP and DGS-1100-26MPP support IEEE 802.3bt, providing up to 90 watts on selected ports for the latest high-powered Pan Tilt Zoom (PTZ) cameras. All switches in the DGS-1100 MP/MPP Series support IEEE 802.3af and 802.3at, providing up to 30 watts per port. This, combined with high power budgets, ensure all of your critical surveillance infrastructure can be powered from a single switch.



Example Surveillance Topology

Surveillance Topology Web Interface Screenshot

**D-Link** Surveillance Mode

Wizard Tools Save Help Online Help Logged in as: admin- 172.18.60.67 Logout

Fuzzy Search

- DGS-1100-26MPP
  - Port Information
  - IP-Camera Information
  - NVR Information
  - PoE Information
  - PoE Scheduling
- Time
  - Surveillance Settings
  - Surveillance Log
  - Health Diagnostic

**Surveillance Overview**

Surveillance Topology Device Information

IP Camera x 12 | NVR x 2 | ! x 1 | Other x 3

Port 7  
IP: 10.90.90.7  
Model: DCS-2136L  
Power Consumption: 3.0 W

D-Link DGS-1100-26MPP

Note: System probes IP-Camera every 30s.

Device Information Web Interface Screenshot

**D-Link** Surveillance Mode

Wizard Tools Save Help Online Help Logged in as: admin- 172.18.60.67 Logout

Fuzzy Search

- DGS-1100-26MPP
  - Port Information
  - IP-Camera Information
  - NVR Information
  - PoE Information
  - PoE Scheduling
- Time
  - Surveillance Settings
  - Surveillance Log
  - Health Diagnostic

**Surveillance Overview**

Surveillance Topology Device Information

SWITCH WEB INFO

|                  |                |             |                   |                   |                                    |
|------------------|----------------|-------------|-------------------|-------------------|------------------------------------|
| Device Type      | DGS-1100-26MPP | IP Address  | 10.90.90.90       | Boot PROM Version | Ver 1.00.002                       |
| System Name      | D-Link         | Mask        | 255.0.0.0         | Firmware Version  | Ver 2.00.05                        |
| Hardware Version | C1             | Gateway     | 10.90.90.254      | System Time       | 1/1/2000 00:06:11                  |
| Serial Number    | T51O19000012   | MAC Address | 00-AD-24-18-F4-3B | Using Time        | 0 days0 hours 6 minutes 11 seconds |

PoE Utilization

MAX 518W | 40%

Bandwidth Utilization

Total Bandwidth | 190 Mbps

Note: System probes IP-Camera every 30s.

| Technical Specifications  |   |   |  |  |
|---------------------------|---|---|--|--|
| General                   | DGS-1100-10MP   | DGS-1100-10MPP  | DGS-1100-26MP  | DGS-1100-26MPP   |
| Hardware Version          | • C1  |   |  |  |
| Size                      | • 11-inch desktop size <sup>1</sup><br>• 1U height  | • 11-inch desktop size <sup>1</sup><br>• 1U height  | • 19-inch rackmount size<br>• 1U height              | • 19-inch rackmount size<br>• 1U height  |
| Number of Ports           | • 8 x 10/100/1000 Mbps PoE<br>• 2 x SFP 1000 Mbps   | • 8 x 10/100/1000 Mbps PoE<br>• 2 x SFP 1000 Mbps   | • 24 x 10/100/1000 Mbps PoE<br>• 2 x Combo 1000 Mbps | • 24 x 10/100/1000 Mbps PoE<br>• 2 x Combo 1000 Mbps   |
| Port Functions            | <ul style="list-style-type: none"> <li>• IEEE 802.3 compliant</li> <li>• IEEE 802.3u compliant</li> <li>• IEEE 802.3ab compliant</li> <li>• IEEE 802.3af/802.3at compliant</li> <li>• IEEE 802.3bt (DGS-1100-10MPP/26MPP only)</li> <li>• IEEE 802.3x Flow Control supports full-duplex mode</li> <li>• Supports manual/auto MDI/MDIX configuration</li> <li>• Auto-negotiation</li> <li>• Supports half/full-duplex operation</li> <li>• IEEE 802.3az compliant</li> </ul> |   |  |  |
| Performance               |   |   |  |  |
| Switching Capacity        | • 20 Gbps   |   | • 52 Gbps  |  |
| Maximum Forwarding Rate   | • 14.88 Mpps  |   | • 38.69 Mpps   |  |
| MAC Address Table Size    | • 8K Entries  |   |  |  |
| Packet Buffer             | • 4.1 Mb  |   |  |  |
| Flash Memory              | • 32 MBytes   |   |  |  |
| PoE                       |   |   |  |  |
| PoE Standard              | • IEEE 802.3af<br>• IEEE 802.3at  | • IEEE 802.3af<br>• IEEE 802.3at<br>• IEEE 802.3bt  | • IEEE 802.3af<br>• IEEE 802.3at                     | • IEEE 802.3af<br>• IEEE 802.3at<br>• IEEE 802.3bt   |
| PoE Capable Ports         | • Ports 1 to 8  |   | • Ports 1 to 24                                      |  |
| PoE Power Budget          | • 130 W<br>• 30 W max. per PoE port   | • 242 W<br>• 30 W max. per PoE port for ports 1 to 6<br>• 90 W max. per PoE port for ports 7 to 8 | • 370 W<br>• 30 W max. per PoE port                  | • 518 W<br>• 30 W max. per PoE port for ports 1 to 20<br>• 90 W max. per PoE port for ports 21 to 24 |
| Power Consumption         |   |   |  |  |
| Standby Mode              | • 4.25 W  | • 5.95 W  | • 12.60 W  | • 13.89 W  |
| Maximum Power Consumption | • 143.14 W (PoE on)<br>• 10.92 W (PoE off)  | • 262.16 W (PoE on)<br>• 10.92 W (PoE off)  | • 405.52 W (PoE on)<br>• 18.12 W (PoE off)           | • 545.51 W (PoE on)<br>• 18.12 W (PoE off)   |
| Physical                  |   |   |  |  |
| Power Input               | <ul style="list-style-type: none"> <li>• 100 to 240 V AC</li> <li>• 50 to 60 Hz internal power supply</li> </ul>  |   |  |  |
| MTBF                      | • 376,888 hours   | • 362,120 hours   | • 269,137 hours                                      | • 295,797 hours  |
| Acoustics                 | • Max.: 51.9 dB(A)<br>• Min.: 36.8 dB(A)  | • Max.: 51.9 dB(A)<br>• Min.: 36.8 dB(A)  | • Max.: 53.7 dB(A)<br>• Min.: 37.8 dB(A)             | • Max.: 53.7 dB(A)<br>• Min.: 37.8 dB(A)   |
| Heat Dissipation          | • 570.51 BTU/hr   | • 570.51 BTU/hr   | • 1470.46 BTU/hr                                     | • 1470.46 BTU/hr   |
| Weight                    | • 1.67 kg (3.68 lbs)  | • 1.77 kg (3.90 lbs)  | • 3.83 kg (8.44 lbs)                                 | • 4.26 kg (9.39 lbs)   |
| Dimensions                | • 294 x 180 x 44 mm<br>(11.57 x 7.08 x 1.73 in)   | • 294 x 180 x 44 mm<br>(11.57 x 7.08 x 1.73 in)   | • 440 x 285 x 43 mm<br>(17.32 x 11.22 x 1.69 in)     | • 440 x 285 x 43 mm<br>(17.32 x 11.22 x 1.69 in)   |
| Ventilation               | • 1 x Fan   |   | • 2 x Fans   |  |
| Operating Temperature     | -10 to 55 °C (14 to 131 °F)   |   |  |  |

|                     |                             |
|---------------------|-----------------------------|
| Storage Temperature | -20 to 70 °C (-4 to 158 °F) |
| Operating Humidity  | 0% to 95% non-condensing    |
| Storage Humidity    | 0% to 95% non-condensing    |
| EMI                 | FCC/IC, CE, VCCI, BSMI, CCC |
| Safety              | cUL, UL, LVD, CB, CCC, BSMI |

| Software Features        |  |   |
|--------------------------|--|---|
| VLAN                     | <ul style="list-style-type: none"> <li>• Port-based VLAN</li> <li>• 802.1Q Tagged VLAN</li> <li>• Auto Surveillance VLAN</li> <li>• Voice VLAN</li> <li>• Management VLAN</li> </ul>   | <ul style="list-style-type: none"> <li>• Asymmetric VLAN</li> <li>• VLAN Group <ul style="list-style-type: none"> <li>• Supports 128 static VLAN groups</li> <li>• Max. 4094 VIDs</li> </ul> </li> </ul>  |
| L2 Features              | <ul style="list-style-type: none"> <li>• Flow Control <ul style="list-style-type: none"> <li>• 802.3x Flow Control</li> <li>• HOL Blocking Prevention</li> </ul> </li> <li>• Jumbo Frames up to 10,240 Bytes</li> <li>• IGMP Snooping <ul style="list-style-type: none"> <li>• IGMP v1/v2 Snooping</li> <li>• Supports 64 Groups</li> <li>• IGMP Snooping Querier</li> </ul> </li> <li>• 802.3ad Link Aggregation: <ul style="list-style-type: none"> <li>• DGS-1100-10MP: Support 5 groups per device and 8 ports per group</li> <li>• DGS-1100-26MP: Support 5 groups per device and 8 ports per group</li> <li>• DGS-1100-10MPP: Support 5 groups per device and 8 ports per group</li> <li>• DGS-1100-26MPP: Support 5 groups per device and 8 ports per group</li> </ul> </li> <li>• Ethernet Ring Protection Switching <ul style="list-style-type: none"> <li>• G.8032 ERPS</li> </ul> </li> <li>• Loopback Detection</li> </ul> | <ul style="list-style-type: none"> <li>• Cable Diagnostics</li> <li>• LLDP</li> <li>• Port Mirroring <ul style="list-style-type: none"> <li>• One-to-One</li> <li>• Many-to-One</li> </ul> </li> <li>• Statistics <ul style="list-style-type: none"> <li>• Tx Ok</li> <li>• Tx Error</li> <li>• Rx Ok</li> <li>• Rx Error</li> </ul> </li> <li>• Spanning Tree Protocol <ul style="list-style-type: none"> <li>• 802.1D STP</li> <li>• 802.1w RSTP</li> </ul> </li> <li>• L2 Multicast <ul style="list-style-type: none"> <li>• MLD Snooping</li> </ul> </li> </ul> |
| Quality of Service (QoS) | <ul style="list-style-type: none"> <li>• 802.1p Quality of Service</li> <li>• 4 queues per port</li> <li>• Queue Handling <ul style="list-style-type: none"> <li>• Strict</li> <li>• Weighted Round Robin (WRR)</li> </ul> </li> </ul>   | <ul style="list-style-type: none"> <li>• Port-based Bandwidth Control (Rate Limiting) <ul style="list-style-type: none"> <li>• Ingress : 16 Kbps, Egress : 16 Kbps</li> </ul> </li> </ul>   |
| Security                 | <ul style="list-style-type: none"> <li>• D-Link Safeguard</li> <li>• Traffic Segmentation</li> <li>• Broadcast/Multicast/Unknown Unicast Storm Control</li> </ul>  | <ul style="list-style-type: none"> <li>• DoS Attack Prevention</li> <li>• SSL</li> </ul>  |
| Management               | <ul style="list-style-type: none"> <li>• Web-based GUI (Supports IPv4/IPv6)</li> </ul>   | <ul style="list-style-type: none"> <li>• Client-based Utility (D-Link Network Assistant Utility)</li> </ul>   |
| Green Technology         | <ul style="list-style-type: none"> <li>• Power Saving by <ul style="list-style-type: none"> <li>• Link Status</li> <li>• LED Shut-Off</li> <li>• Port Shut-Off</li> <li>• System Hibernation</li> </ul> </li> </ul>  | <ul style="list-style-type: none"> <li>• Compliant with IEEE 802.3az Energy-Efficient Ethernet</li> </ul>   |
| MIB/RFC Standards        | <ul style="list-style-type: none"> <li>• RFC768 UDP</li> <li>• RFC791 IP</li> <li>• RFC792 ICMP</li> <li>• RFC793 TCP</li> <li>• RFC826 ARP</li> <li>• RFC1213 MIB II</li> <li>• RFC1493 Bridage MIB</li> <li>• RFC1907 SNMPv2 MIB</li> <li>• RFC1215 MIB Traps Convention</li> </ul>  | <ul style="list-style-type: none"> <li>• RFC2233 Interface Group MIB</li> <li>• RFC2665 Ether-like MIB</li> <li>• RFC4363 IEEE 802.1p MIB</li> <li>• ZoneDefense MIB</li> <li>• Private MIB</li> <li>• RFC951 BootP client</li> <li>• RFC1542 BootP/DHCP client</li> <li>• RFC2236 IGMP Snooping</li> </ul>   |

# DGS-1100 MP/MPP Series Gigabit Ethernet PoE Switches

| Order Information         |  |
|---------------------------|--|
| <i>Part Number</i>        | <i>Description</i>   |
| DGS-1100-10MP             | 8-Port 10/100/1000 Mbps + 2-Port SFP 1000 Mbps PoE switch                          |
| DGS-1100-26MP             | 24-Port 10/100/1000 Mbps + 2-Port Combo 1000BASE-T/SFP PoE switch                  |
| DGS-1100-10MPP            | 8-Port 10/100/1000 Mbps + 2-Port SFP 1000 Mbps PoE switch                          |
| DGS-1100-26MPP            | 24-Port 10/100/1000 Mbps + 2-Port Combo 1000BASE-T/SFP PoE switch                  |
| Optional SFP Transceivers |  |
| DEM-210                   | 100BASE-FX, single-mode, 15 km   |
| DEM-211                   | 100BASE-FX, multi-mode, 2 km   |
| DEM-220T                  | 100BASE-BX-D , single-mode, 20 km  |
| DEM-220R                  | 100BASE-BX-U , single-mode, 20 km  |
| DGS-712                   | 1000BASE-T copper, 100 m   |
| DEM-310GT                 | 1000BASE-LX, single-mode, 10 km  |
| DEM-311GT                 | 1000BASE-SX, multi-mode, 550 m   |
| DEM-312GT2                | 1000BASE-SX, multi-mode, 2 km  |
| DEM-314GT                 | 1000BASE-LHX, single-mode, 50 km   |
| DEM-315GT                 | 1000BASE-ZX, single-mode, 80 km  |
| DEM-330T                  | 1000BASE-BX-D, single-mode, 10 km  |
| DEM-330R                  | 1000BASE-BX-U, single-mode, 10 km  |
| DEM-331T                  | 1000BASE-BX-D, single-mode, 40 km  |
| DEM-331R                  | 1000BASE-BX-U, single-mode, 40 km  |
| DIS-301SX                 | 1000BASE-SX, multi-mode, 550 m, 850 nm, -40 to 85 °C wide operating temperature    |
| DIS-302SX                 | 1000BASE-SX, multi-mode, 2 km, 1310 nm, -40 to 85 °C wide operating temperature    |
| DIS-310LX                 | 1000BASE-LX, single-mode, 10 km, 1310 nm, -40 to 85 °C wide operating temperature  |
| DIS-S330EX                | 1000BASE-EX, single-mode, 30 km, 1310 nm, -40 to 85 °C wide operating temperature  |
| DIS-S350LHX               | 1000BASE-LHX, single-mode, 50 km, 1550 nm, -40 to 85 °C wide operating temperature |
| DIS-S380ZX                | 1000BASE-ZX, single-mode, 80 km, 1550 nm, -40 to 85 °C wide operating temperature  |

<sup>1</sup> 19-inch rack-mounting brackets included.

Updated 2019/05/09