

Product type

Wireless Microphone Systems

Type

Handhelds

Transmission frequency range

655 - 679 MHz

Weight

5,435 kg

LDU506R2 - LD Systems U506 R2 Dual receiver

Product type

Wireless Microphone System Accessories

Type

true diversity

Modulation Type

FM

Channels

2 x 96 (8 groups of 12 channels)

Groups

8

Antenna inputs

2

Antenna connector

BNC

Frequency response

60 - 16.000 Hz

Signal-to-noise ratio

> 105 dB

Noise reduction

Squelch

Audio output, balanced

2 x XLR

Controls

volume headphones

Indicators

2 x audio level , 2 x HF level A/B , 2 x multifunction LC display

Operating voltage

1,000 mA , 13.5 V DC

Audio mix output, balanced

XLR

Audio mix output, unbalanced

6.3 mm jack

Max. output level

symmetrical -8 dBu

Headphones output

1

Headphones outputs

6.3 mm TRS

Weight

2,05 kg

Other features

channel search function , IR frequency synchronisation

Width

483 mm

Height

45 mm

Depth

190 mm

Accessories (included)

2 x antenna , Batteries , Power supply

**[LDU506MC - LD Systems U506 MC Condenser
handheld microphone](#)**

Type
Microphones

Channels
160

Groups
10

Microphone type
condenser

Directivity
Cardioid

Signal-to-noise ratio
95 dB

Rated HF output power
Variable (2mW, 10mW, 30mW)

Controls
Power

Indicators
multifunction LC display

Operating voltage
2 x AA battery

Operating time
>10 h (with alkaline batteries)

Length
255 mm

Diameter
49 mm

Weight
0,25 kg

Other features
incl. batteries